


## **Recommended Specifications**


The sectional overhead "Pirie Bar Panel" shall be manufactured to comply with Pirie Enterprises Pty Ltd quality assurance programme. External framing and vertical muntins to be  $50.8 \times 50.8 \times 50.8$ 



The door shall consist of panels hinged together to negotiate the curve of the track and a fixed matching head panel if required. The number of panels in each door shall be as recommended by the manufacturer. Each panel shall be fitted with rollers running in the side tracks, hardware and hinges hangers shall be made from galvanised or zincannealed steel. Hinges , hangers shall be fabricated from 2mm thick sheet. Tracks shall be fabricated from 1.6mm sheet and shall be curved where necessary to required radius and mounted on mild steel brackets fixed to the building structure by approved means. Horizontal runs shall be reinforced with mild steel angles. Springs shall be helical wound torsion springs mounted on a 25mm torsion bar with alloy cable drums attached. Galvanized lifting cables to be used. Engineers wind load specification 50mps for doors up to 20 sq. metres.

## FOR FURTHER INFORMATION CONTACT MANUFACTURERS





Other products available: Manufacturers of Industrial, Commercial, Domestic Automatic Doors and Gates • Structural Aluminium

• Architecturally designed Sectional Overhead Doors • Aluminium Louvres & Vents • Glass bricks Pre Fab or Fire Rated • Fire Doors • Parking Systems



Showroom: 22 Industrial Avenue, Southport 4215 Phone: **07 5539 6644** 

Fax: **07 5539 6988** A.B.N. 16 009 731 113

**AGENT:-**